



Material: Hot dip galvanized steel.

s.r.l. GORLA  
MORSETTERIE  
MILANO

TECHNICAL OFFICE

EXTENSION LINK

EYE-EYE

DRG. N. AT21/X

Rev. 1 dated 28.02.14

Page 2/3

X	A	B	C	D	E	F	G	CR [kN]	
LS630.0	40	0	21.5	-	-	-	-	-	
LS630.1	44	60±1	17.5	17.5	21.5	60	22	120	
LS630.2	44	60±1	21.5	21.5	21.5	60	22	210	
LS630.3	44	80±1	17.5	17.5	21.5	60	22	120	
LS630.4	44	100±1	17.5	17.5	21.5	60	22	120	
LS630.5	44	100±1	21.5	17.5	21.5	60	22	120	
LS630.6	44	100±1	21.5	21.5	21.5	60	22	210	
LS630.7	60	100±1	28.5	28.5	21.5	60	22	360	
LS630.8	44	177±2	17.5	17.5	21.5	60	22	120	
LS630.9	44	186±2	21.5	21.5	21.5	60	22	210	
LS630.10	44	188±2	21.5	21.5	21.5	60	22	210	
LS630.11	60	196±2	28.5	28.5	21.5	60	22	360	
LS630.12	44	470±3	21.5	21.5	21.5	60	22	210	
LS630.13	44	250±2	21.5	21.5	21.5	60	22	210	
LS630.14	44	281±2	21.5	21.5	21.5	60	22	210	
LS630.15	44	301±2	17.5	17.5	21.5	60	22	120	
LS630.16	44	323±2	17.5	17.5	21.5	60	22	120	
LS630.17	44	334±2	21.5	21.5	21.5	60	22	210	
LS630.18	44	376±2	17.5	17.5	21.5	60	22	120	
LS630.19	44	420±3	21.5	21.5	21.5	60	22	210	
LS630.20	44	469±3	17.5	17.5	21.5	60	22	120	
LS630.21	44	265±3	21.5	21.5	21.5	60	22	210	
LS630.22	44	1100±5	21.5	21.5	21.5	60	22	210	
LS630.23	44	600±4	21.5	21.5	21.5	60	22	210	
LS630.24	44	615±4	17.5	17.5	21.5	60	22	120	
LS630.25	44	696±4	21.5	21.5	21.5	60	22	210	
LS630.26	44	800±4	21.5	21.5	21.5	60	22	210	
LS630.27	44	875±4	21.5	21.5	21.5	60	22	210	
LS630.28	44	1150±5	21.5	21.5	21.5	60	22	210	
LS630.29	44	1400±5	21.5	21.5	21.5	60	22	210	
LS630.30	60	300±2	28.5	28.5	21.5	60	22	360	
LS630.31	60	600±4	28.5	28.5	21.5	60	22	360	
LS630.32	44	360±3	21.5	21.5	21.5	60	22	210	
LS6598	44	150±2	17.5	17.5	17.5	40	22	120	
LS6865FS	40	135±2	17.5	17.5	21.5	45	22	120	





